



### Main

Range of product	ConneXium
Product or component type	Ethernet TCP/IP firewall
Concept	Transparent Ready
Communication port protocol	Ethernet TCP/IP SSH HTTP HTTPS SNMP SFTP SCP LLDP RS232
Port Ethernet	10/100BASE-TX - 2 port(s) copper cable
Cybersecurity	IPSec DoS prevention
User interface	Built-in firewall
Encryption protocol	MAC addresses filtering

### Complementary

Integrated connection type	Shielded RJ45 copper cable
Transmission support medium	Twisted shielded pairs cable CAT 5E for copper cable
Maximum cable distance between devices	100 m copper cable
Ethernet service	Multicast filtering
Redundancy	Redundant power supplies
[Us] rated supply voltage	12...48 V
Supply voltage limits	9.6...60 V DC SELV 18...30 V AC SELV
Power consumption in W	5 W
Electrical connection	Removable connector 6 ways power supply
Mounting support	35 mm symmetrical DIN rail
Marking	CE
Local signalling	2 LEDs (green) for P1 P2 power supplies 1 LED (red) for fault 1 dual colour LED (green/yellow) for device status 1 dual colour LED (green/yellow) for memory key status 1 dual colour LED (green/yellow) for internal port status 1 dual colour LED (green/yellow) for serial port status
Alarm output	1 voltfree contact 1 A
Alarm function	Power supply fault Data link status Switch fault
Ethernet cabling system	TF switches
Width	60 mm
Height	145 mm
Depth	125 mm
Net weight	0.66 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.



## Environment

Ambient air temperature for operation	-40...70 °C
Relative humidity	10...95 % non-condensing
IP degree of protection	IP20
Directives	2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility
Standards	UL 508 EN/IEC 61131 EN/IEC 60950
Product certifications	CE UL RCM DNV

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	860 g
Package 1 Height	14.5 cm
Package 1 width	6.1 cm
Package 1 Length	12.8 cm
Unit Type of Package 2	S04
Number of Units in Package 2	2
Package 2 Weight	2.22 kg
Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm

## Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

## Contractual warranty

Warranty	18 months
----------	-----------

Dimensions

