



### Main

|                             |   |
|-----------------------------|---|
| Range of product            | ConneXium   |
| Product or component type   | Ethernet TCP/IP firewall  |
| Concept                     | Transparent Ready   |
| Communication port protocol | Ethernet TCP/IP<br>SSH<br>HTTP<br>HTTPS<br>SNMP<br>SFTP<br>SCP<br>LLDP<br>RS232 |
| Port Ethernet               | 10/100BASE-TX - 2 port(s) copper cable  |
| Cybersecurity               | Syslog protocol support<br>IPSec  |
| User interface              | Built-in firewall   |
| Encryption protocol         | MAC addresses filtering   |

### Complementary

|  |  |
|--|--|
| Integrated connection type             | Shielded RJ45 copper cable   |
| Transmission support medium            | Twisted shielded pairs cable CAT 5E for copper cable   |
| Maximum cable distance between devices | 100 m copper cable   |
| Ethernet service                       | Multicast filtering<br>Syslog  |
| Communication service                  | Port monitoring  |
| Diagnostics run time                   | Signal contact<br>Self test<br>MAC notification  |
| Redundancy                             | Redundant network coupling<br>Router redundancy  |
| [Us] rated supply voltage              | 12...48 V  |
| Supply voltage limits                  | 9.6...60 V DC SELV<br>18...30 V AC SELV  |
| Power consumption in W                 | 6.9 W  |
| Electrical connection                  | Removable connector 6 ways power supply  |
| Mounting support                       | 35 mm symmetrical DIN rail   |
| Marking                                | CE<br>UL<br>RCM  |
| Function available                     | System information<br>Report<br>IP Firewall list<br>Configuration check<br>Reachability test (ping)<br>Alarms (Traps)  |
| Local signalling                       | 2 LEDs (green) for P1 P2 power supplies<br>1 LED (red) for fault<br>1 dual colour LED (green/yellow) for device status<br>1 dual colour LED (green/yellow) for memory key status<br>1 dual colour LED (green/yellow) for internal port status<br>1 dual colour LED (green/yellow) for serial port status |
| Alarm output                           | 1 voltfree contact 1 A   |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                         |   |
|-------------------------|---|
| Alarm function          | Power supply fault<br>Data link status<br>Switch fault<br>High temperature<br>External memory removed |
| Ethernet cabling system | TF switches   |
| Width                   | 60 mm   |
| Height                  | 145 mm  |
| Depth                   | 125 mm  |
| Net weight              | 0.61 kg   |

## Environment

|                                       |  |
|---------------------------------------|--|
| Ambient air temperature for operation | -40...70 °C  |
| Relative humidity                     | 10...95 % non-condensing   |
| IP degree of protection               | IP20   |
| Directives                            | 2014/35/EU - low voltage directive<br>2014/30/EU - electromagnetic compatibility |
| Standards                             | UL 508<br>EN/IEC 61131<br>EN/IEC 60950   |
| Product certifications                | CE<br>UL<br>RCM<br>DNV   |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Weight             | 1.05 kg |
| Package 1 Height             | 21 cm   |
| Package 1 width              | 22 cm   |
| Package 1 Length             | 22.5 cm |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)  <a href="#">EU RoHS Declaration</a>  |
| Mercury free               | Yes   |
| RoHS exemption information |  Yes   |
| China RoHS Regulation      |  <a href="#">China RoHS Declaration</a>  |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Dimensions

