

Just Right



PE4000B
Atom™ N2600 Model



PE4000B
Atom™ N270 Model

Highly compact IPC empowering your applications

Various interfaces for transparent production processes

Pro-face mobility solutions for remote access

Compact size and low power consumption



Specification

		Atom™ N2600 Model	Atom™ N270 Model
CPU		Intel®Atom™ Dual Core N2600 1.6 GHz	Intel®Atom™ N270 1.6 GHz
Main Memory		2 GB or 4 GB (DDR3 800 MHz)	2 GB (DDR2 533 MHz)
FAN		FAN less	
Rated Input Voltage		12 to 24 Vdc ±5 %	9 to 36 Vdc ±5 %
Power Consumption		Typically 16 W	Typically 15 W
Supported OS		Windows®Embedded Standard 2009 (32bit) or Windows®Embedded Standard 7 (32bit)	Windows® Embedded Standard 2009 (32bit)
Surrounding Air Temperature		0 to 60°C [32 to 140 °F] (with air flow, speed = 0.7 m/sec.) 0 to 50°C [32 to 122 °F] (without airflow)	0 to 70°C [32 to 150 °F] (with airflow, speed=0.7m/sec) 0 to 60°C [32 to 140 °F] (without airflow)
Interface	Ethernet	10/100/1000 Mbit/s x 3	10/100/1000 Mbit/s x 1
	USB	USB 2.0 x 5	USB 2.0 x 2
	Serial	RS-232C x 2, RS-232C/422/485 x 4	RS-232C x 2
	Video	Analog RGB x 1, HDMI x 1	Analog RGB x 1
	Expansion Slot	Mini PCIe (full size) x 1	Mini PCIe (half size) x 1
	Digital I/O	8 points (selectable I/O)	-
	Others	Line out, Mic-in, Line in	PS2 x 1
Storage		SSD x 1	
		CFast x 1	CF x 1
External Dimensions		264.5 x 69.2 x 133 mm (10.41 x 2.72 x 5.24 in.)	254.8 x 58.7 x 149.2 mm (10.03 x 2.31 x 5.88 in.)

Lineup

Storage / OS	Atom™ N2600 Model	Atom™ N270 Model
SSD (80GB) / WES7	PFXPEBBD42DNN1	-
CFast (16GB) / WES7	PFXPEBBD42CNN1	-
CFast (8GB) / WES2009	PFXPEBBD21BNN1	-
CF (8GB) / WES2009	-	PFXPEBAD21ANN1
None	PFXPEBBD40NNN1	PFXPEBAD20NNN1

Options

Model	Product Name	
Storage	PFXZPESSD81	SSD unit 80GB for PE-4000B
	PFXZPESSD161	SSD unit 160GB for PE-4000B
	PFXZPECF81	CF Card 8GB for PE-4000B
	PFXZPECFA82	CFast Card 8GB for PE-4000B
	PFXZPECFA162	CFast Card 16GB for PE-4000B
Adaptor	PFXZPEAFDR1	DIN rail Adaptor for N270
	PFXZPEAFDR2	DIN rail Adaptor for N2600
	PFXZPECNHDDV1	HDMI-DVI connector *1
EZ Series*2	PFXZCCEUSG1	EZ Illuminated Switch
	PFXZCCEUKB1	EZ Numpad
Maintenance	PFXZPECNDC1	DC power supply connector for N270
	PFXZPECNDC2	DC power supply connector for N2600
	PFXZPECNIO1	DIO Connector

Software

Model	Product Name Product Description
(Web Download)	Pro-face Remote HMI Software to operate Pro-face HMI screen on any iOS or Android device.
	Pro-face Remote HMI Server The Pro-face Remote HMI Server is a Windows S/W to connect any IPC or PC with our Pro-face Remote HMI APP and operate any kind of S/W via the APP.
PFXEXRHLSL	Pro-face Remote HMI Server
PFXEXSDVV**	Pro-Server EX Ver.** *3 Software that connects a PC to most Pro-face HMIs via Ethernet for data collection and transmission.
PFXEXEDV**	GP-Pro EX Ver.** Screen-creation software
	Win GP for IPC Runtime license on Pro-face's IPC, for using the screen data created with the screen editor GP-Pro EX.

*1 : Separately prepare a clamp to prevent the connector from being disconnected before use. *2 : USB options can only be used together with the Win GP software.
*3 : The Pro-Server EX can only be used in Client mode in conjunction with Win GP.

WARNING

HAZARD OF OPERATOR INJURY, OR UNINTENDED EQUIPMENT DAMAGE

Before operating any of these products, be sure to read all related manuals thoroughly.

Failure to follow these instructions can result in death, serious injury or unintended equipment damage.

- For printing purposes, the colors in this catalog may differ from those of the actual unit.
- All product names used in this catalog are the registered trademarks or trademarks of their respective companies.
- Actual user screens may differ from the screens shown here.
- All information contained in this catalog is subject to change without notice.
- Electric equipment should be installed, operated, serviced, and maintained only by qualified personnel. No responsibility is assumed by Digital for any consequences arising out of the use of this material.

For detailed information, visit our website.

<http://www.pro-face.com/product/ipc/pe4000b/>



Pro-face
for the best interface

Visit our website for more information.
<http://www.proface.com>

Global Headquarters
Digital Electronics Corporation
[JAPAN] Tel: +81-(0)6-6613-1101
[AUSTRALIA] Tel: +61 (0)3 9550 7396
[DENMARK] Tel: +45 70 22 01 22
[GERMANY] Tel: +49 (0)212 258 260
[ITALY] Tel: +39 0362 59 96 1
[SOUTH KOREA] Tel: +82-(0)2-2630-9850
[SWITZERLAND] Tel: +41 (0)43 343 7272
[SINGAPORE] Tel: +65-6832-5533

North/South American Headquarters
Pro-face America, Inc.
[U.S.A.] Tel: +1-734-477-0600
[AUSTRIA] Tel: +43 7236 3343 620
[ENGLAND] Tel: +44 (0)2476 511288
[INDIA] Tel: +91 80 4333 3540
[POLAND] Tel: +48 22 465 66 62
[SPAIN] Tel: +34 (0)93 846 07 45
[TAIWAN] Tel: +886-(0)2-2657-1121

European Headquarters
Pro-face Europe B.V.
[THE NETHERLANDS] Tel: +31 (0)23 55 44 099
[CHINA] Tel: +86-(0)21-6361-5175
[FRANCE] Tel: +33 (0)1 60 21 22 91
[INDONESIA] Tel: +62 21 750 4496
[RUSSIA] Tel: +7 (812)336 47 06
[SWEDEN] Tel: +46 46 540 90 70
[THAILAND] Tel: +66-(0)2-617-5678