

# 15" Flat Panel Monitor - FP3710T



**Features:**

- XGA Display TFT Touch Panel
- VESA Mounting (75mm)
- DVI Compatible
- Rugged Aluminum Body
- 16 million colors
- NEMA 4/4x/12 Rated (IP65F) \*Not using Front USB
- RoHS Directive-conforming
- Front USB interface (FP3710-T42-U only)

**Performance Specifications**

Model	FP3710-T42-U FP3710-T42
Display Type	TFT Color LCD (15 inch)
Display Colors	16,777,216 Colors
Display Area	304.1mm [11.97in.] x 228.1mm [8.98 in.]
Video	VGA Interface (analog RGB) Connector or DVI-D*1 Interface Connector
Graphics Display Resolution	XGA (1024 x 768 pixels)
Backlight	CCFL (Replaceable)
Contrast Adjustment	Adjustable via OSD
Touch Screen	RS-232C or USB (Type B, USB 2.0 compatible) *1
USB (type A)*2	Front port (USB 2.0 compatible) (FP3710-T42-U only)


\*1 Use one or the other.  
\*2 Available for use when the touch panel USB cable (B type) is connected to a PC.

**General Specifications**

Model	FP3710-T42 and FP3710-T42-U (AC Model)
Input Voltage	AC100V to 240V (50/60Hz)
Power Consumption	AC100 V1.1A or less, AC240 V0.7A or less
Allowable Voltage Drop	1 cycle or less (Voltage drop interval must be 1s or more.)
Voltage Endurance	AC1500V 20mA for 1 minute
Insulation Resistance	DC500V 10MΩ(min.) (between charging and FG terminals)
Certifications	UL508, CSA-C22.2 No.142-M1987, CE (EN55011 Class A, EN61000-6-2, EN60950-1), RoHS
Ambient Operating Temperature*3	0 to 50°C (32 to 122°F) (within 30° from the installing angle vertical direction)
Humidity - Ambient/Storage	10 to 90% RH (Not condensing, wet bulb temperature: 39°C (84.2°F) or less). Storage Temperature -20 to +60°C (-4 to 140°F)
Corrosive Gas	Free of corrosive gases
Noise Immunity	Noise Voltage: 1500Vp-p, Pulse Duration: 50ns, 500ns, 1μs Rise Time: 1ns (via noise simulator)
Electrostatic Discharge Immunity	6kV (complies with EN 61000-4-2 Level 3)
Vibration Resistance	JIS B 3502, IEC61131-2 compatible, 5Hz to 9Hz Half Amplitude 3.5mm, 9Hz to 150Hz Constant Acceleration 9.8m/s2, Applied in X, Y and Z directions 10 cycles for 100 minutes
Rating	Equivalent to IP65f (only for the front area when the panel is installed)*4
Weight	Approx. 7.0kg [15.4lb]
External Dimensions	395mm [15.55in.] W x 294mm [11.57in.] H x 60mm [2.36in.] D
Warranty	Two (2) year

\*3 "Ambient Operating Temperature" indicates the cabinet interior or panel face temperature.  
\*4 Meets IP65f testing requirements. Operation is not, however, guaranteed in every environment.

**FP3710T - External Dimensions - North American Version**



**Ordering Information**

Part Number	Description
FP3710-T42	15" TFT Color LCD
FP3710-T42-U	15" TFT Color LCD, Front port (Type A USB 2.0 compatible)

**Accessories or Replacement Components**



Product Name		Part Number
Touch Interface		
Serial Interface Cable	5m	FP61V-IS00-O
USB Cable	5m	FP-US00
Video Interface		
Analog RGB Cable	4.5m	FP-CV02-45
DVI-D Cable	5m	FP-DV01-50
Installation Fasteners *1		CA3-ATFALL-01
Backlight (2 pieces/set for 1 unit) *1		CA7-BLU15-01
Screen Protection Sheet (5 sheets/set)		CA3-DFS15-01

\*1Standard attachment for all models.

Caution: Before operating any of these products, please be sure to read all related manuals thoroughly.

- All product names used in this document are trademarks or registered trademarks of their respective companies.
- All information contained in this document is subject to change without notice.

**FP3710T - Cut-Out Dimensions - North American Version**



**Pro-face America**  
Phone: 734.429.4971  
Fax: 734.429.1010  
www.profaceamerica.com

**Customer Service Hotline: 734.944.0482**

For more information  
**ACCESS** [www.profaceamerica.com](http://www.profaceamerica.com)



## California Proposition 65 Warning—Lead and Lead Compounds

## Advertencia de la Proposición 65 de California—Plomo y compuestos de plomo

## Avertissement concernant la Proposition 65 de Californie—Plomb et composés de plomb

**⚠ WARNING:** This product can expose you to chemicals including lead and lead compounds, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to: [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**⚠ ADVERTENCIA:** Este producto puede exponerle a químicos incluyendo plomo y compuestos de plomo, que es (son) conocido(s) por el Estado de California como causante(s) de cáncer y defectos de nacimiento u otros daños reproductivos. Para mayor información, visite : [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**⚠ AVERTISSEMENT:** Ce produit peut vous exposer à des agents chimiques, y compris plomb et composés de plomb, identifiés par l'État de Californie comme pouvant causer le cancer et des malformations congénitales ou autres troubles de l'appareil reproducteur. Pour de plus amples informations, prière de consulter: [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

All trademarks are the property of Schneider Electric SE, its subsidiaries, and affiliated companies.

**Schneider Electric USA, Inc.**  
800 Federal Street  
Andover, MA 01810 USA  
888-778-2733  
[www.schneider-electric.us](http://www.schneider-electric.us)

Todas las marcas comerciales son propiedad de Schneider Electric SE, sus filiales y compañías afiliadas.

Importado en México por:  
**Schneider Electric México, S.A. de C.V.**  
Av. Ejercito Nacional No. 904  
Col. Palmas, Polanco 11560 México, D.F.  
55-5804-5000  
[www.schneider-electric.com.mx](http://www.schneider-electric.com.mx)

Toutes les marques commerciales sont la propriété de Schneider Electric SE, ses filiales et compagnies affiliées.

**Schneider Electric Canada, Inc.**  
5985 McLaughlin Road  
Mississauga, ON L5R 1B8 Canada  
800-565-6699  
[www.schneider-electric.ca](http://www.schneider-electric.ca)